
SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Product Name: Turbo BeerKeeper
- Product Part Number: D-TUBK

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Use of the substance/mixture: Beer Line Cleaner

1.3 Details of the supplier of the safety data sheet

- Name of Supplier: Chemisphere UK Ltd
- Address of Supplier: Unit 4 Richmond Road
Trafford Park
Manchester
M17 1RE
- Telephone: +44 (0) 161 874 7200
- Responsible Person: Wilfred Worsley
- Email: safetydata@chemisphereuk.co.uk

1.4 Emergency telephone number

- Emergency Telephone: +44 (0) 776 724 8499

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- CLP: Skin Corr. 1A

2.2 Label elements



GHS05

- Signal Word: Danger
- Hazard statements
Causes severe skin burns and eye damage.
Toxic to aquatic life.
- Precautionary statements
Keep out of reach of children.
Wear protective gloves/protective clothing/eye protection/face protection.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Get immediate medical advice/attention.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

SECTION 2: Hazards identification (....)

Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Get medical advice/attention if you feel unwell.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

If skin irritation occurs: Get medical advice/attention.

If medical advice is needed, have product container or label at hand.

Contains: Potassium hydroxide

Sodium hypochlorite

- Supplemental Hazard information (EU)
Contact with acids liberates toxic gas.

2.3 Hazards identification

- Not a PBT according to REACH Annex XIII
-

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

- Sodium carbonate
CAS Number: 497-19-8
EC Number: 207-838-8
Concentration: < 5%
Categories: Eye Irrit. 2
Symbols: GHS07
H Statements: H319
- Potassium hydroxide
CAS Number: 1310-58-3
EC Number: 215-181-3
Concentration: 1 - 20%
Categories: Acute Tox. 4, Skin Corr. 1A
Symbols: GHS05;GHS07
H Statements: H302;H314
- Sodium hypochlorite, solution ... % Cl active
CAS Number: 7681-52-9
EC Number: 231-668-3
Concentration: < 5%
Categories: Skin Corr. 1B; Aquatic Acute 1
Symbols: GHS05,GHS09
H Statements: H314,H400,EUH031
- Potassium permanganate
CAS Number: 7722-64-7
EC Number: 231-760-3
Concentration: < 1%

SECTION 3: Composition/information on ingredients (....)

Categories: Ox. Sol. 2; Acute Tox. 4; Aquatic Acute 1; Aquatic Chronic 1
Symbols: GHS03,GHS07,GHS09
H Statements: H272,H302,H400,H410

SECTION 4: First aid measures

4.1 Description of first aid measures

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

4.2 Most important symptoms and effects, both acute and delayed

- Contact with eyes
Causes severe burns
Risk of serious damage to eyes
May cause permanent damage if eye is not immediately irrigated.
- Ingestion
Causes severe burns
Causes damage to the digestive tract if swallowed
- Inhalation
Corrosive to the respiratory tract.
Can cause damage to the respiratory system
- Contact with skin
Corrosive to skin
Causes severe burns

4.3 Indication of any immediate medical attention and special treatment needed

- If medical advice is needed, have product container or label at hand.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Not flammable. In case of fire use extinguishing media appropriate to surrounding conditions

5.2 Special hazards arising from the substance or mixture

- May give off noxious and toxic fumes in a fire

5.3 Advice for firefighters

- Wear chemical protection suit and breathing apparatus
-

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

SECTION 6: Accidental release measures (....)

- Wear protective clothing as per section 8
- Avoid contact with skin and eyes
- Avoid breathing dust/fume/gas/mist/vapours/spray.

6.2 Environmental precautions

- For large spills:. Do not allow product to enter drains. For small spills:. Flush down the drain with plenty of water.

6.3 Methods and material for containment and cleaning up

- Absorb spillage in inert material and shovel up

6.4 Reference to other sections

- Wear protective clothing as per section 8
-

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Wear protective gloves/protective clothing/eye protection/face protection.
- Avoid contact with skin and eyes
- Do not breathe vapour/fumes
- Do not mix with any other products
- Proper chemicals handling procedures should be adopted
- Handle and open container with care
- Ensure adequate ventilation

7.2 Conditions for safe storage, including any incompatibilities

- Keep locked up and out of reach of children
- Keep only in the original container in a cool, well ventilated place away from acid
- Incompatible with acid
- Protect from sunlight.

7.3 Specific end use(s)

- Beer line cleaning.
-

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

- Sodium carbonate
DNEL (Industry; inhalational, long term local effects): 10 mg/m³
DNEL (Consumer; inhalational, long term local effects): 1 mg/m³
 - Potassium hydroxide
DNEL (Industry; inhalational, long term local effects): 1 mg/m³
DNEL (Consumer; inhalational, long term local effects): 1 mg/m³
 - Sodium hypochlorite, solution ... % Cl active
DNEL (Industry; inhalational, long term local effects): 1.55 mg/m³
DNEL (Consumer; inhalational, long term local effects): 1.55 mg/m³
DNEL (Consumer; inhalational, short term local effects): 3.1 mg/m³
-

SECTION 8: Exposure controls/personal protection (....)

- Potassium permanganate
DNEL (Industry; inhalational, long term local effects):
DNEL (Consumer; inhalational, long term local effects):
DNEL (Consumer; inhalational, long term systemic effects): 0.039 mg/m³
DNEL (Industry; inhalational, long term systemic effects): 0.218 mg/m³

8.2 Exposure controls

- Wear protective gloves/protective clothing/eye protection/face protection.

**Gloves****Goggles**

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- Appearance: Liquid, dark
- Odour: Slight smell of chlorine
- pH: >13
- Density: 1.16 g/cm³ at 20 deg C
- Conductivity: Not available
- Solubility in water: Soluble in water
- Flammability: Not flammable

9.2 Other information

- No information available
-

SECTION 10: Stability and reactivity**10.1 Reactivity**

- Reacts with acid

10.2 Chemical stability

- Considered stable under normal conditions

10.3 Possibility of hazardous reactions

- Contact with acid may form toxic gases

10.4 Conditions to avoid

- Keep away from heat, light and moisture

10.5 Incompatible materials

- Avoid contact with acid
- Avoid contact with aluminium
- Avoid contact with zinc
- Avoid contact with tin

10.6 Hazardous decomposition products

SECTION 10: Stability and reactivity (....)

- No hazardous decomposition products known
-

SECTION 11: Toxicological information

11.1 Contact with eyes

- Causes serious eye damage.

11.2 Ingestion

- Causes damage to the digestive tract
- Causes damage to the stomach lining

11.3 Inhalation

- Corrosive to the respiratory tract.

11.4 Contact with skin

- Causes severe burns

11.5 Information on toxicological effects

- Sodium carbonate
LD50 (oral, rat): 2800 mg/kg
LD50 (dermal) : 2000 mg/kg
LC50 (inhalation, rat): 2300 mg/l
 - Potassium hydroxide
LD50 (oral, rat): 333 mg/kg
 - Sodium hypochlorite, solution ... % Cl active
LD50 (oral, rat): > 1200 mg/kg
LD50 (dermal) : > 2000 mg/kg
LC50 (inhalation, rat): 10500 mg/l
 - Potassium permanganate
LD50 (oral, rat): > 2000 mg/kg
LD50 (dermal) : > 2000 mg/kg
-

SECTION 12: Ecological information

12.1 Toxicity

- Sodium carbonate
EC50 (daphnia): 265 mg/l (48 hr)
LC50 (fish): 300 mg/l (96 hr)
- Potassium hydroxide
EC50 (daphnia): 40-240 mg/l (48 hr)
LC50 (fish): 80 mg/l (96 hr)
- Sodium hypochlorite, solution ... % Cl active

SECTION 12: Ecological information (....)

LC50 (fish): 0.06 mg/l (96 hr)

- Potassium permanganate
EC50 (daphnia): 0.15 mg/l (48 hr)
LC50 (fish): 1.51 mg/l (96 hr)

12.2 Persistence and degradability

- Not readily biodegradable

12.3 Bioaccumulative potential

- No information available

12.4 Mobility in soil

- Soluble in water

12.5 Results of PBT and vPvB assessment

- Not a PBT according to REACH Annex XIII

12.6 Other adverse effects

- No information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information



Corrosive

14.1 UN number

- UN No.: 3266

14.2 Proper Shipping Name

- Proper Shipping Name: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (potassium hydroxide)

14.3 Transport hazard class(es)

- Hazard Class: 8

14.4 Packing group

- Packing Group: II.

14.5 Environmental hazards

- None assigned

14.6 Special precautions for user

SECTION 14: Transport information (....)

- Identification Number: 80
- IMDG EmS: F-A, S-B
- Tunnel Code: (E)
- Contains: Potassium hydroxide

14.7 Emergency Action Code

- 2R

14.8 Transport in bulk according to Annex II of Marpol and the IBC Code

- Not applicable
-

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- This Safety Data Sheet is provided in compliance with the EC Regulation 1907/2006-2015/830

15.2 Chemical safety assessment

- A chemical safety assessment (CSA) for this product has not yet been completed
-

SECTION 16: Other information

Text not given with phrase codes where they are used elsewhere in this safety data sheet:- EUH031: Contact with acids liberates toxic gas. H272: May intensify fire; oxidiser. H302: Harmful if swallowed. H314: Causes severe skin burns and eye damage. H319: Causes serious eye irritation. H400: Very toxic to aquatic life. H410: Very toxic to aquatic life with long lasting effects.

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

--- end of safety datasheet ---
